Docket No.: M&R 3.0-039

The present Amendment is in response to the Office Action mailed May 5, 2006, in the above-identified application. Enclosed herewith is a Petition requesting a three-month extension of time for resetting the deadline for responding to the Office Action from August 5, 2006, to and including November 5, 2006.

REMARKS

Applicant notes that the present application includes independent claim 1, with claims 2-6 and 19-21 depending therefrom, and independent claim 7, with claims 9-13 and 22-24 depending therefrom.

In the present Amendment, claim 7 has been amended to incorporate the limitations of claim 8 therein and claim 8 has been canceled.

the Office Action, the Examiner rejected In claims 1-2, 19 and 21 under 35 U.S.C. §102(b) as being anticipated by U.S. Patent No. 3,478,682 to Funahashi. Referring to FIG. 3 thereof, Funahashi discloses a multi-color rubber stamp including rubber letter blocks 10 having engraved surfaces 10'. Stainless letter steel partition plates 8 are positioned between each of the adjacent rubber letter blocks 10 to prevent the mixing of different colored inks from one block to an adjacent block.

In contrast, referring to FIG. 3 thereof, in certain preferred embodiments of the present invention, a first foam sheet 30 includes a substantially non-porous top surface 32 having images flash-printed thereon, a bottom, untreated surface 34 that remains substantially porous and peripheral edges 36 that extend between the substantially non-porous top surface 32 and the substantially porous bottom surface 34. A cutting device, such as a laser, may be used for cutting a plurality of first marking structures 38A-38F that are substantially similar

Docket No.: M&R 3.0-039

to one another. Each first marking structure 38 includes an edge 40 that defines a unique pattern for assembly with another marking structure, as will be described in more detail below. As noted above, in certain preferred embodiments, each first marking structure 38A-38F is cut using a laser. As the laser cuts through the first foam sheet 30, the edges of the individual first marking structures 38A-38F are preferably exposed to the energy of the laser for melting the foam edges of the first marking structures 38. As a result, the edges become non-porous so that ink may not pass therethrough. Other cutting devices, such as cutting knives, razors, dies, presses and water may also be used to form the first marking structures 38A-38F. In all of these other cutting methods, energy must be applied to at least one of the edges of the first marking structures to form at least one non-porous edge.

FIG. 3 also shows a second foam sheet 42 having a top surface 44, a bottom surface 46 and peripheral edges 48 extending between top surface 44 and bottom surface 46. The second foam sheet 42 is treated in a similar fashion as described above with respect to first foam sheet 30, so that top surface 44 is substantially non-porous, except for the flag design, and the bottom surface 46 is substantially porous. Second marking structures 50A-50F are cut from the second foam structures second sheet 42. The 50A-50F marking are substantially similar to one another and include a unique pattern 52 preferably cut using a laser (or one of the other cutting devices listed above). As the laser cuts through the second marking structures 50A-50F, the peripheral edge surfaces are melted for forming non-porous surfaces through which ink may not pass.

In order to create a marking structure for a hand stamp, one of the first marking structures 38 from the first foam

sheet 30 is assembled with one of the second marking structures 50 from the second foam sheet 42. The edge pattern 40 of the first marking structure 38 may be assembled with the edge pattern 52 of a second marking structure 50 in only one orientation. This is due to the unique patterns cut into the first and second marking structures 38, 50.

In certain preferred embodiments, the first marking structure 38 is loaded with red ink so that the stripes 54 of the flag are red and white (in non-porous areas) and the second marking structure 50 is loaded with blue ink so that the field 56 of the flag is blue. After the first and second marking structures 38, 50 are assembled together, it is desirable to prevent the red ink of the first marking structure 38 from mixing with the blue ink of the second marking structure 50. As such, the non-porous edges of the first and second marking structures prevent mixing of the ink. Of critical importance, the non-porous edges also preclude the need for a third object, such as a barrier or border, to be assembled between the opposing edges of the two marking structures 38, 50, thereby simplifying the assembly process and minimizing the number of parts needed for assembly.

Examiner's rejection, In response the to Applicant respectfully asserts that Funahashi does not teach or suggest a hand stamp including "said first and second marking structures being permanently assembled together so that at least one of said edges of said first marking structure opposes at least one of said edges of said second marking structure, wherein at least one of said opposing edges has a non-porous surface for preventing migration of said first ink of said first marking structure with said second ink of said second marking structure." Clearly, Funahashi provides no teaching that "at least one of said opposing edges [of a

marking structure] has a non-porous surface" for preventing migration of ink. Funahashi teaches using an extra component, i.e., a stainless steel partition plate, to prevent ink mixing. For the above reasons, claim 1 is unanticipated by Funahashi and is otherwise allowable. Claim 2 is unanticipated, inter alia, by virtue of its dependence from claim 1, which is unanticipated for the reasons set forth above.

Applicant respectfully asserts that claim 19 is unanticipated by Funahashi because the reference does not teach a hand stamp, "wherein said opposing edges of said first and second marking structures are in contact with one another." Claim 19 is also unanticipated, inter alia, by virtue of its dependence from claim 1, which is unanticipated for the reasons set forth above.

Applicant also asserts that claim 21 is unanticipated by Funahashi because the reference does not teach a hand stamp, "wherein said non-porous surface is integral with one of said first and second marking structures." In Funahashi, the non-porous surface is provided by a stainless steel partition plate 8 that is positioned between adjacent rubber letter blocks The reference does not teach that the "non-porous surface 10. integral with one of said first and second marking structures," as required by claim 21. For these reasons, claim 21 is unanticipated by Funahashi and is otherwise allowable. Claim 21 is also unanticipated, inter alia, by virtue of its dependence from claim 1, which is unanticipated for the reasons set forth above.

The Examiner rejected claims 1-2, 4, 19 and 21 under 35 U.S.C. §102(b) as being anticipated by U.S. Patent No. 5,653,804 to Yashoshima. The Examiner asserts that Yashoshima teaches providing an ink blocking layer 8 between adjacent ink pads 3. Thus, this reference is very similar to

Funahashi, which teaches providing partition plates 8 between adjacent rubber letter blocks 10 (FIG. 3).

In response to the Examiner's rejection, Applicant respectfully asserts that claim 1 is unanticipated by Yashoshima because the cited reference does not disclose a hand stamp including "a first marking structure having . . . peripheral edges extending between said front and rear surfaces" and "a second marking structure having . . . peripheral edges extending between said front and rear surfaces . . . said first and second marking structures being permanently assembled together so that at least one of said edges of said first marking structure opposes at least one of said edges of said second marking structure, wherein at least one of said opposing edges has a non-porous surface for preventing migration of said first ink of said first marking structure with said second ink of said second marking structure." Claims 2 and 4 are unanticipated, inter alia, by virtue of their dependence from claim 1.

Claim 19 is unanticipated by Yashoshima because the reference does not teach or suggest a hand stamp "wherein said opposing edges of said first and second marking structures are in contact with one another." Clearly, as shown in FIG. 3 of Yashoshima, the adjacent ink pads 3 do not have opposing edges that are in contact with one another. In fact, the adjacent ink pads 3 are separated from one another by ink blocking layer 8. For these reasons, claim 19 is unanticipated by Yashoshima and is otherwise allowable. Claim 19 is also unanticipated by virtue of its dependence from claim 1, which is unanticipated for the reasons set forth above.

Claim 21 is unanticipated by Yashoshima because the reference neither discloses nor suggests a hand stamp

"wherein said non-porous surface is integral with one of said first and second marking structures." Referring to FIG. 3 thereof, Yashoshima's ink blocking layer 8 is not "integral with one of said first and second marking structures" but is a separate piece placed between two adjacent ink pads 3. For these reasons, claim 21 is unanticipated by Yashoshima and is otherwise allowable. Claim 21 is also unanticipated by virtue of its dependence from claim 1, which is unanticipated for the reasons set forth above.

The Examiner rejected claims 7 and 9 under 35 U.S.C. §102(b) being anticipated by U.S. as No. 3,988,987 to Ikura et al. Referring to FIGS. 1-3 thereof, Ikura et al. discloses a combination stamp 1 having a plurality of stamp elements 2, each of which includes a stamp frame 3 made of a resin. Each stamp frame 3 has a rectangular cross-section with a top wall 3a and four sidewalls 3b, 3c, 3d, and 3e. One sidewall 3b includes a dovetail-like vertical interlocking projection 5, and another sidewall 3c has a dovetail-like vertical interlocking groove 6. The vertical projection 5 is fitted into the vertical groove 6 to join adjacent stamp elements 2 together and to prevent horizontal displacement of the adjacent stamp elements 2.

In response to the Examiner's rejection, Applicant respectfully notes that Ikura's two stamp elements 2, shown in FIGS. 2 and 3 thereof, can be assembled in more than one configuration. FIG. 2 shows two adjacent stamp elements 2 that are assembled together. In FIG. 3, Ikura shows a first stamp element 2 (on the left) having a dovetail-like projection 5 that is assembled with a dovetail-like groove 6 of a second stamp element 2 (on the right). However, the first stamp element can be decoupled from the left side of the second stamp element and reassembled with the right side of

stamp element, whereby the the second dovetail-like projection on the right side of the second stamp element is assembled with a dovetail-like groove on the left side of the first Ikura's stamp elements element. Thus, stamp assembled in more than one configuration. For the above reasons, Applicant respectfully asserts that claim unanticipated by Ikura et al. because the reference neither suggests that the "first and second teaches nor structures can be assembled together in only one configuration." Clearly, Ikura's stamp frames can be assembled together in more than "only one configuration." For the above reasons, claim 7 is unanticipated by Ikura et al. and is otherwise allowable. Claim 9 is unanticipated, inter alia, by virtue of its dependence from claim 7, which is unanticipated for the reasons set forth above.

In the Office Action, the Examiner rejected claims 3 and 6 under 35 U.S.C. §103(a) as being unpatentable over Funahashi in view of U.S. Patent No. 6,119,596 to Fletcher The Examiner acknowledges that Funahashi does not et al. explicitly disclose a pre-inked marking structure and a mixture of thermoplastic resin/ink. The Examiner contends, however, that Fletcher teaches a stamp that discloses a pre-inked marking structure that includes a mixture of thermoplastic resin/ink and that it would have been obvious at the time the invention was made to one having ordinary skill in the art to modify the invention taught by Funahashi to include a pre-inked marking structure with a mixture of thermoplastic resin/ink as taught by In response, Applicant respectfully asserts that Fletcher. Fletcher does not overcome the deficiencies noted above in Thus, claims 3 and 6 are unobvious, inter alia, by Funahashi. virtue of their dependence from claim 1, which is unobvious for the reasons set forth above.

Docket No.: M&R 3.0-039

The Examiner rejected claim 5 under 35 U.S.C. §103(a) as being unpatentable over Funahashi in view of U.S. Patent No. 6,000,335 to Imamaki et al. The Examiner has cited Imamaki as teaching the formation of a non-porous surface by applying a light source that melts the microporous stamping member. In response, Applicant respectfully asserts that Imamaki does not overcome the deficiencies noted above in Funahashi, and that claim 5 is patentable, inter alia, by virtue of its dependence from claim 1, which is patentable over Funahashi for the reasons set forth above.

Claims 8 and 11 are rejected under 35 U.S.C. §103(a) as being unpatentable over Ikura et al. in view of Funahashi. In response, Applicant respectfully notes that claim 8 has been canceled, and that, with respect to claim 11, Funahashi does not overcome the deficiencies noted above in Ikura et al.

The Examiner rejected claims 10 and 13 under 35 U.S.C. §103(a) as being unpatentable over Ikura et al. in view of U.S. Patent No. 6,119,596 to Fletcher et al. In response, Applicant respectfully asserts that Fletcher et al. does not overcome the deficiencies noted above in Ikura et al.

The Examiner rejected claims 12 and 20 under 35 U.S.C. §103(a) as being unpatentable over Ikura et al. in view of Imamaki et al. In response, Applicant respectfully asserts that Imamaki does not overcome the deficiencies noted above in Ikura and that claim 12 is also unobvious by virtue of its dependence from claim 7 which is unobvious for the reasons set forth above.

Claim 20, which depends from claim 1, is unobvious over the art of record because the references neither disclose nor suggest a hand stamp "wherein said non-porous surface comprises melted microporous foam that prevents ink from passing therethrough." Referring to FIG. 3 thereof, Funahashi uses a

stainless steel partition plate 8 for providing a non-porous surface that prevents ink migration. Ikura discloses a plastic frame that functions as a non-porous surface for preventing ink migration. The non-porous surfaces do not comprise "melted microporous foam." For these reasons, claim 20 is patentable over the references cited by the Examiner and is otherwise allowable.

The Examiner rejected claims 22 and 24 under 35 U.S.C. §103(a) as being unpatentable over Ikura in view of U.S. Patent No. 3,446,143 to Williamson. Referring to FIG. 8 thereof, Williamson teaches a structure including a first section 30 and a second section 31 that are assembled together. The first section 30 is loaded with a first color ink and the second section 31 is loaded with a second color ink that is different than the first color ink. In response, Applicant notes that independent claim 7 has been amended to incorporate the limitations of claim 8 therein, and that claims 22 and 24 depend from claim 7. Thus, claims 22 and 24 contain the limitations found in claim 7. In view of the above noted amendment, Applicant respectfully asserts that claims 22 and 24 are unobvious over Ikura in view of Williamson because the cited references neither disclose nor suggest a hand stamp "wherein at least one of the interlocked first and second patterned peripheral edges has a non-porous surface for preventing ink migration between said first and second marking structures."

The Examiner rejected claim 23 under 35 U.S.C. §103(a) as being unpatentable over Ikura in view of Funahashi. In response, Applicant respectfully asserts that claim 23 is unobvious, inter alia, by virtue of its dependence from claim 22, which is unobvious for the reasons set forth above. Claim 23 is also unobvious because Funahashi does not overcome the deficiencies noted above in Ikura.

As it is believed that all of the rejections set forth in the Office Action have been fully met, favorable reconsideration and allowance are earnestly solicited.

If, however, for any reason the Examiner does not believe that such action can be taken at this time, it is respectfully requested that she telephone Applicant's attorney at (908) 654-5000 in order to overcome any additional objections which she might have.

If there are any additional charges in connection with this requested Amendment, the Examiner is authorized to charge Deposit Account No. 12-1095 therefor.

Dated: October 31, 2006

Respectfully submitted,

Michael J. Doherty

Registration No.: 40,592 LERNER, DAVID, LITTENBERG,

KRUMHOLZ & MENTLIK, LLP

600 South Avenue West

Westfield, New Jersey 07090

(908) 654-5000

Attorney for Applicant

679406_1.DOC